

NOUS41 KWBC 091912 AAA
PNSWSH

Technical Implementation Notice 16-13 Amended
National Weather Service Headquarters Washington DC
920 AM EDT Fri Jun 10 2016

To: Subscribers:
-NOAA Weather Wire Service
-Emergency Managers Weather Information Network
-NOAAPORT
-Other NWS Partners, Users and Employees

From: Tim McClung
Portfolio Manager
Office of Science and Technology Integration

Subject: Amended: Changes to Gridded Localized Aviation Model
Output Statistics Program (LAMP) Effective June 14,
2016

Notice amended to clarify dissemination paths for new and existing Gridded LAMP products. On the change date, the new elements described in (1) and (2) below will be available in the operational National Digital Guidance Database (NDGD), but will not be disseminated on the Satellite Broadcast Network (SBN) or NOAAPORT until such time as there is sufficient bandwidth available to accommodate these new products. Existing Gridded LAMP products will continue to be disseminated on the SBN/NOAAPORT and to NDGD.

On or about Tuesday, June 14, 2016, beginning with the 1200 Coordinated Universal Time (UTC) model run, the NWS Meteorological Development Laboratory (MDL) will implement changes to the Gridded Localized Aviation Model Output Statistics Program (LAMP).

Gridded LAMP products are generated on a 2.5-km Lambert Conformal grid over the CONUS. Gridded observations and gridded forecasts (1 to 25 hour projections) are produced hourly.

The changes are as follows:

1. Add seven new elements to LAMP gridded forecast guidance for CONUS. Guidance will be available for the following new elements:

- 10-m wind gusts
- Probability of ceiling height less than 500 ft
- Probability of ceiling height less than 1000 ft
- Probability of ceiling height less than or equal to 3000 ft
- Probability of visibility less than 1 mile
- Probability of visibility less than 3 miles

- Probability of visibility less than or equal to 5 miles

2. Add one new element to LAMP gridded observations for CONUS.

Gridded LAMP observations will be available for the following new elements:

- 10-m wind gusts

3. Minor algorithm changes and updated station lists for station input into Gridded LAMP are expected to provide slight improvements to the Gridded LAMP observations and forecast guidance for existing elements:

- 2-m Temperature
- 2-m Dewpoint temperature
- Ceiling height
- Visibility
- Sky Cover
- 10-m Wind speed
- 10-m Wind direction

Specifically,

- The criteria to reject input points have been modified slightly.
- The gridding algorithm for temperature and dewpoint now utilizes upper air data, which is expected to improve accuracy of the Gridded LAMP temperature and dewpoint observations and forecasts at higher elevations in the mountainous regions.
- The gridding algorithm and smoothing have been modified slightly and the station list has been updated for ceiling height, visibility, and sky cover.

Benefits of the system changes include:

- Availability of Gridded LAMP gridded observations and forecasts guidance for new element of 10-m wind gusts
- Availability of Gridded LAMP gridded forecasts for new elements of ceiling height probabilities and visibility probabilities
- In general, expected slight improvements in the gridded fields due to additional data and minor algorithm modifications
- Expected improved accuracy of Gridded LAMP temperature and dewpoint observations and forecasts at higher elevations in the mountainous regions
- Ceiling and visibility observations and forecasts gridded data now better fit the underlying point data and reduce the spread of very low ceiling and visibility values into areas on the grid where there are no nearby station points.

Dissemination:

On the change date, the new elements described in (1) and (2) above will be available in the operational National Digital Guidance Database (NDGD), but will not be disseminated on the

Satellite Broadcast Network (SBN) or NOAAPORT until such time as there is sufficient bandwidth available to accommodate these new products. Existing Gridded LAMP products will continue to be disseminated on the SBN/NOAAPORT and to NDGD.

The gridded LAMP products for the CONUS, in GRIB2 format, are available on the NWS server at:

<ftp://tgftp.nws.noaa.gov/SL.us008001/ST.opnl/DF.gr2/DC.ndgd/GT.gtmp/AR.conus/>
or
<http://tgftp.nws.noaa.gov/SL.us008001/ST.opnl/DF.gr2/DC.ndgd/GT.gtmp/AR.conus/>

A listing of the GRIB2 file names for gridded observations and forecasts for new and existing elements is available at:

http://www.weather.gov/mdl/lamp_gtmp_NWS_tgftp_server

The new communication identifiers for the GRIB2 products are shown below in Tables 1 and 2. A complete list of GLMP WMO headers is available at

http://www.weather.gov/media/mdl/gtmpheaders_2016.pdf

Table 1: Communication identifiers for the Gridded LAMP observation products in GRIB2 format

Listed below are representations of the WMO header: xx represents the valid UTC hour (00-23).

WMO HEADER	ELEMENT
-----	-----
LAUAxx KMDL	2-meter gridded temperature observations
LAUBxx KMDL	2-meter gridded temperature observation error estimations
LBUAxx KMDL	2-meter gridded dewpoint temperature observations
LBUBxx KMDL	2-meter gridded dewpoint temperature observation error estimations
LCUAxx KMDL	Gridded ceiling height observations
LDUAxx KMDL	Gridded visibility observations
LEUAxx KMDL	Gridded opaque sky cover observations
LFUAxx KMDL	10-m gridded wind speed observations
LGUAxx KMDL	10-m gridded wind direction observations
LHUAxx KMDL	10-m gridded wind gust observations

Table 2: Communication identifiers for the Gridded LAMP forecast products in GRIB2 format

Listed below are representations of the WMO header: xx represents the forecast projections (01-25).

WMO HEADER	ELEMENT
------------	---------

LKUAXX KMDL Gridded 2-meter temperature forecasts
LLUAXX KMDL Gridded 2-meter dewpoint temperature forecasts
LMUAXX KMDL Gridded ceiling height forecasts
LNUAXX KMDL Gridded visibility forecasts
LOUAXX KMDL Gridded opaque sky cover forecasts
LPUAXX KMDL 10-m gridded wind speed forecasts
LQUAXX KMDL 10-m gridded wind direction forecasts
LRUAXX KMDL 10-m gridded wind gust forecasts
LMUCXX KMDL Gridded probability of ceiling height less
than 500 ft forecasts
LMUDXX KMDL Gridded probability of ceiling height less than
1000 ft forecasts
LMUFXX KMDL Gridded probability of ceiling height less than
or equal to 3000 ft forecasts
LNUCXX KMDL Gridded probability of visibility less than
1 mile forecasts
LNUEXX KMDL Gridded probability of visibility less than
3 mile forecasts
LNUFXX KMDL Gridded probability of visibility less than or
equal to 5 mile Forecasts

More details about the Gridded LAMP products and this implementation, including a link to a website for displaying the new and improved products, can be found online at:

http://www.weather.gov/mdl/lamp_docs

A consistent parallel feed of data is available on the NCEP HTTP. The data are available at the following URL:

<http://para.nomads.ncep.noaa.gov/pub/data/nccf/noaaport/glamp/>

If you have technical comments or questions, please contact:

Judy Ghirardelli
National Weather Service
Meteorological Development Laboratory
Judy.Ghirardelli@noaa.gov
301-427-9496

Links to the LAMP products and descriptions can found at:

http://www.weather.gov/mdl/lamp_home

National Public Information Statements are online at:

<http://www.weather.gov/os/notif.htm>

NNNN