

IX.3.0B-SYSTEM-UPRFLD SUBROUTINE UPRFLD

Description

Subroutine UPRFLD prints the values of the arguments in the call to subroutine UFIELD [[Hyperlink](#)].

Calling Sequence

CALL UPRFLD (NFLD, ISTRT, LENGTH, ITYPE, NREP, INTEGR, REAL, LCHAR, CHAR, LLPAR, LRPAR, LASK, LATSGN, LAMPS, LEQUAL, ISTAT)

Argument List

<u>Argument</u>	<u>Input/ Output</u>	<u>Type</u>	<u>Dimension</u>	<u>Description</u>
NFLD	Input	I*4	1	See note 1 /
ISTRT	Input	I*4	1	See note 1 /
LENGTH	Input	I*4	1	See note 1 /
ITYPE	Input	I*4	1	See note 1 /
NREP	Input	I*4	1	See note 1 /
INTEGR	Input	I*4	1	See note 1 /
REAL	Input	I*4	1	See note 1 /
LCHAR	Input	I*4	1	See note 1 /
CHAR	Input	A4	LCHAR	See note 1 /
LLPAR	Input	I*4	1	See note 1 /
LRPAR	Input	I*4	1	See note 1 /
LASK	Input	I*4	1	See note 1 /
LATSGN	Input	I*4	1	See note 1 /
LAMPS	Input	I*4	1	See note 1 /
LEQUAL	Input	I*4	1	See note 1 /
ISTAT	Input	I*4	1	See note 1 /

Notes:

1/ See Section IX.3.OB-UFIELD [[Hyperlink](#)].