

### IX.3.5C-SYSTEM-PDATAS COMMON BLOCK PDATAS

#### Purpose

Common block PDATAS contains frequently used constants for the Processed Data Base.

#### Listing

```
COMMON /PDATAS/ LBLNK,ZAPR,IDSI,MAXREC(10),MONEY,IZAP,IASTR,LRECLT,  
                LENHED,LENHDC,NUMFIL
```

#### Description of Variables

| <u>Variable</u> | <u>Type</u> | <u>Dimension</u> | <u>Word<br/>Position</u> | <u>Description</u>                           |
|-----------------|-------------|------------------|--------------------------|--|
| IBLNK           | I*4         | 1                | 1                        | A word with 4 blank characters               |
| ZAPR            | R*4         | 1                | 2                        | Value of -999.0                              |
| IDSI            | I*4         | 1                | 3                        | Contains characters DSI                      |
| MAXREC          | I*4         | 1                | 4-13                     | Unused                                       |
| MONEY           | I*4         | 10               | 14                       | Contains the character \$                    |
| IZAP            | I*4         | 1                | 15                       | Value of -999                                |
| IASTR           | I*4         | 1                | 16                       | Contains character *                         |
| LRECLT          | I*4         | 1                | 17                       | Logical record length of time series records |
| LENHED          | I*4         | 1                | 18                       | Length of time series header (expanded)      |
| LENHDC          | I*4         | 1                | 19                       | Length of time series header (compacted)     |
| NUMFIL          | I*4         | 1                | 20                       | Number of time series files                  |