

IX.3.5C-SYSTEM-PMAXDM COMMON BLOCK PMAXDM

Purpose

Common block PMAXDM contains system and user defaults and Processed Data Base control information.

Subroutine RPDBCI fills the common block by reading from the Processed Data Base.

Subroutine WPDBCO writes the values in the common block to the Processed Data Base.

Listing

```
COMMON /PMAXDM/ NAMERF(2),MAXDTP,MAXTMS,MINDAY,MAXDAT,MAXDUM(6),  
              NUMTMS,NUMDTP,NUMDUM(46)
```

Description of Variables

<u>Variable</u>	<u>Type</u>	<u>Dimension</u>	<u>Word Position</u>	<u>Description</u>
NAMEFR	A4	2	1	User identifier
MAXDTP	I*4	1	3	Maximum number of data types
MAXTMS	I*4	1	4	Maximum number of time series
MINDAY	I*4	1	5	Minimum number of days of regular data to be kept when writing to a time series containing regular and future data
MAXDAT	I*4	1	6	Maximum number of data words in a time series
MAXDUM	I*4	6	7	Unused
NUMTMS	I*4	1	13	Number of time series defined
NUMDTP	I*4	1	14	Number of data types defined
NUMDUM	I*4	46	15	Unused