

COMMON BLOCK XTIME

Purpose

Holds current day timing information for the MAP function. Basic timing values held in FCTIME (see IX.3.2C-FCTIME).

Listing

COMMON /XTIME/ KZDA, KDA, KHR, LSTMO, KMO, KID, KYR, KIH, TZCODE, ISW, IUTMP,
NSSR, IDAY

Size

13 words

Description of Variables

<u>Variable</u>	<u>Type</u>	<u>Dim.</u>	<u>Word Pos.</u>	<u>Description</u>
KZDA	I	1	1	Current Julian day (Z time clock).
KDA	I	1	1	Current Julian day (internal clock).
KHR	I	1	3	Ending hour for the current day (internal clock).
LSTMO	I	1	4	Month number at the start of the current day (local standard time).
KMO	I	1	5	Current month for output.
KID	I	1	6	Current day for output.
KYR	I	1	7	Current year for output (4 digits).
KIH	I	1	8	Last hour of current day for output.
TZCODE	A	1	9	Output time zone code.
ISW	I	1	10	Summer/winter switch for current day = 0, summer = 1, winter.
IUTMP	I	1	11	Unit number for the temporary file for the current day.

Word

<u>Variable</u>	<u>Type</u>	<u>Dim.</u>	<u>Pos.</u>	<u>Description</u>
NSSR	I	1	12	Number of stranger reports for the current day.
IDAY	I	1	13	Initial day indicator = 0, not initial day of run = 1, initial day of run.