

B-6. Log Files

Several of the RAX applications generate log files. This section provides a list of the applications that generate log files and lists the locations of the log files. More detailed information on these log files can be found in the specific application's documentation.

➤ **adbinit suite**

Log files for this suite of applications are written to the same directory **that** the applications are located in, `/rfc_arc/bin/adbinit`. For detailed information about the log files, see section E-1, part 4.0.

➤ **shef_decode_raw**

The `shef_decode_raw` application has two types of log files, individual message output files and a daily log file. These files can be found at the following locations, `/rfc_arc/logs/decoder/raw/err` and `/rfc_arc/logs/decoder/raw/logs`, respectively. For detailed information about the log files, see section F-1, parts 4.0, 5.0 and 6.0.

➤ **shef_decode_pro**

The `shef_decode_pro` application has two types of log files, individual message output files and a daily log file. These files can be found at the following locations, `/rfc_arc/logs/decoder/processed/err` and `/rfc_arc/logs/decoder/processed/logs`, respectively. For detailed information about the log files, see section F-2, parts 4.0, 5.0 and 6.0.

➤ **check_raw_decoder, check_processed_decoder**

The log files for these two scripts, which normally run in oper's cron, are written to the `/rfc_arc/logs/decoder/check` directory. For more information, see section F-4.

➤ **level 1 processors**

Log files for this suite of applications are written to the `/rfc_arc/logs/process` directory. For detailed information about the log files, see section G-2, part 4.0.

➤ **get_states**

The log file for this application is located in the directory `/rfc_arc/logs/nwsrfs`. For more information, see section H-1.

➤ **get_params**

The log file for this application is located in the directory `/rfc_arc/logs/nwsrfs`. For more information, see section H-2.

➤ **group_parse**

The log file for this application is located in the directory `/rfc_arc/logs/nwsrfs`. For more information, see section H-3.

➤ **loadmods, fetchmods**

The log file for this application is located in the directory `/rfc_arc/logs/nwsrfs`. For more information, see section H-4.

➤ **cron_PGbkups**

The log file for this application is located in the directory `/rfc_arc/logs/dbadmin`. For more information, see section M-2.

➤ **run_vacuumdb**

The log file for this application is located in the directory `/rfc_arc/logs/dbadmin`. For more information, see section M-4.

➤ **rax_status_df**

The log file for this application is located in the directory `/rfc_arc/logs/sysadmin`. For more information, see section M-8, part 3.0.

➤ **purge_files**

The log file for this script is located in the directory `/rfc_arc/logs/purgefiles`. For more information, see section M-10.

➤ **Postgres Engine**

The log file for the Postgres engine is located in the directory /var/log. For more information on this log file, refer to the PostgreSQL web site, <http://www.postgresql.org>.